

## Architectural Abstract

### Aquarock<sup>™</sup> GYPSUM BASED CEILINGS


- Made with BPB's proprietary Enhanced Glass Reinforced Gypsum substrate.
- Moisture Resistant.
- Mold Resistant Core.
- Vinyl Faced.
- Sag Resistant.
- Exceptional indoor/outdoor performance in ceiling applications up to 100% relative humidity.
- Perfect for exterior soffits and canopies, parking garages, pools, spas, commercial kitchens, and locker, shower or therapy rooms.
- Scrubbable USDA/FSIS accepted CRF vinyl facing seals out moisture.
- Non-combustible core panel resists damage from blunt impact and chemical fumes.



Item Number	Nominal Size (Inches)	Edge Detail	NRC	CAC	LR	Sq. Ft. Per Carton
<b>Safetone<sup>®</sup> Class A</b>						
<b>White CRF</b>						
1182-CRF-15V	24 x 24 x 1/2	Trim	-	43	.88	32
1180-CRF-15V	24 x 48 x 1/2	Trim	-	43	.88	32

ASTM E 1264 Classification: Type XX, Pattern G

#### Edge Detail



**Trim Edge**  
(Square) 1<sup>5</sup>/<sub>16</sub>" Grid

#### Finish



White CRF - CRF-1

#### Popular Applications:

- Exterior Soffits • Exterior Canopies
- Parking Garages • Pools • Spas
- Commercial Kitchens • Locker Rooms
- Shower Rooms • Food Processing



# PRODUCT SPECIFICATION DETAILS

## ACOUSTICAL CEILING SYSTEMS

### 09500

## PART 2: PRODUCTS

### 2.1 GENERAL

Provide acoustical ceiling material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XX (gypsum base)
2. Form NA
3. Pattern G
4. 100% RH gypsum board lay-in panel with fine textured vinyl finish [White CRF]
5. Size 1/2" thick x [24"x 24"] [24"x 48"]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) NA
8. Ceiling Attenuation Class (CAC) 43
9. Light Reflectance Coefficient (LR) .88  
Light Reflectance Designation LR-1
10. Color: White
11. Flame Spread Classification Class A
12. Manufacturer, subject to compliance with requirements of this specification, BPB
13. Product Name Capaul® Brand Aquarock™

#### Size Options

24" x 24"

24" x 48"

Distributed by:

#### USA

**BPB America Inc.**  
5301 West Cypress St., Suite 300  
Tampa, FL 33607  
Toll Free: +1-866-427-2872  
Fax: +1-800-829-1422  
E-mail: [crc@bpb-na.com](mailto:crc@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

#### Canada

**BPB Canada Inc.**  
Architectural Products Sales Division  
6715 Ogdendale Road SE  
Calgary, Alberta T2C 2A4  
Toll Free: +1-866-427-2872  
Fax: +1-800-829-1422  
E-mail: [crc@bpb-na.com](mailto:crc@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

#### Outside North America

**BPB America Inc.**  
5301 West Cypress St., Suite 300  
Tampa, FL 33607  
Phone: +1-813-286-3900  
Fax: +1-813-286-3908  
E-mail: [international@bpb-na.com](mailto:international@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

®™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-3990 Rev. C/3M/0605

