

Architectural Abstract

Cashmere® Custom Options

Cashmere® Invisigrille™

Invisigrille™ Integrated Speaker Panels

- Upscale appearance.
- Factory painted fabric to conceal speaker openings.
- Panels identical to Cashmere® ceiling texture.
- Eliminates ceiling plane clutter associated with obtrusive metal or plastic grilles.
- BioShield™ feature included as standard feature for added mold and mildew resistance.

See reverse side for additional product specifications.

How to Specify Invisigrille™:

Add prefix (I) before designated Cashmere® item number. For example:
Item #CM-450 with Invisigrille™. Specify #(I) CM-450


Note: All Invisigrille™ openings are round and available only in standard white.

Cashmere® Custom Options available only on 24" x 24" ceiling panels.




Invisigrille™ Integrated Speaker Panels*


Edge Detail Options




Radius Reveal Edge
5/16" Grid




Reveal Edge
(Beveled) 1/4" Grid



Tier Reveal Edge
5/16" Grid



Narrow Reveal Edge
(Corner Bevel) 5/16" Grid



Narrow Reveal Edge
(Corner Bevel)
5/16" Grid (Bolt Slot)



BioShield™

BioShield treatment included for added mold and mildew resistance.



Popular Applications:

- Conference Centers • Resorts • Hospitality •
- Retail • Education • Restaurants • Healthcare •
- Offices • Airports • Galleries



PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.


2.1 Materials

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern [E] [E K]
4. Lightly textured [face scored] nodulated lay-in panels
5. Size 3/4" thick x [12"x 12"] [24"x 24"] [24"x 48"] [20"x 60"] [30"x 30"]
5. Size 3/4" thick x 24"x 24"
6. Edge Detail [Reveal] [Narrow Reveal] [Radius Reveal] [Bevel Reveal] [Tier Reveal] [Narrow Reveal Screw Slot]
7. Light Reflectance Coefficient (LR) .82
Light Reflectance Designation LR-1
8. Color White
9. Flame Spread Classification Class A
10. Manufacturer, subject to compliance with requirements of this specification, BPB
11. Product Name Celotex® Brand Cashmere® Invisigrille™


Face Scoring Options

Unscored



- (I) CMR-124
- (I) CMB-124
- (I) CMTS-124
- (I) CM-454
- (I) CM-450

Face Scored



- (I) CMR-412
- (I) CMB-412
- (I) CMTS-412

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogdendale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4704 Rev. E/W/0405

