

Architectural Abstract

Cashmere® Designer Series

NODULAR ACOUSTICAL CEILING PANELS

- Upscale appearance.
- Finely textured pattern.
- Clean linear scoring.
- Scored options for added visual impact.
- BioShield™ feature included as standard feature for added mold and mildew resistance.


See reverse side for additional product specifications.




Item Number	Nominal Size (Inches)	Edge Detail	UL Classified NRC	UL Classified CAC	LR	Sq. Ft. Per Carton
Safetone® Class A						
CDS-224	24 x 48 x 3/4	Reveal	.60	35	.82	64
CDSN-224	24 x 48 x 3/4	Narrow Reveal	.60	35	.82	64
CDS-448	24 x 48 x 3/4	Reveal	.60	35	.82	64
CDSN-448	24 x 48 x 3/4	Narrow Reveal	.60	35	.82	64
CDS-812	24 x 48 x 3/4	Reveal	.60	35	.82	64
CDSN-812	24 x 48 x 3/4	Narrow Reveal	.60	35	.82	64

ASTM E 1264 Classification: Type III, Form 1, Pattern E K

Edge Detail Options




Reveal Edge
(Beveled) 1/16" Grid




Narrow Reveal Edge
(Beveled) 1/16" Grid


Scoring Options



24" x 48"
224



24" x 48"
448



24" x 48"
812



BioShield™
BioShield treatment **included** for added mold and mildew resistance.



Popular Applications:

- Resorts • Conference Rooms • Airports • Hospitality • Retail
- Offices • Education • Healthcare • Restaurants • Salons



PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 1
3. Pattern E, K
4. Lightly textured surface scored to simulate [two 24"x 24"] [four 6"x 48"] [eight 12"x 12"] nodular lay-in panel
5. Size 3/4" thick x 24"x 48"
6. Edge Detail, Lay-in panels: [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) .60
8. Ceiling Attenuation Class (CAC) 35
9. Light Reflectance Coefficient (LR) .82
Light Reflectance Designation LR-1
10. Color White
11. Flame Spread Classification Class A
12. Manufacturer, subject to compliance with requirements of this specification, BPB
13. Product Name Celotex® Brand Cashmere® Designer Series

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogdendale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4703 Rev. F/W/0505

