

Architectural Abstract

School Board®

WET-FELTED ACOUSTICAL CEILING PANELS


- Up to 25% higher surface hardness than conventional wet-felted ceiling products per ASTM C367 testing.
- High light reflectance suitable for indirect lighting applications.

See reverse side for additional product specifications.

Item Number	Nominal Size (Inches)	Edge Detail	UL Classified NRC	UL Classified CAC	LR	Sq. Ft. Per Carton
Safetone® Class A						
SB-150	24 x 24 x 5/8	Narrow Reveal	.50	35	.85	64
SB-154	24 x 24 x 5/8	Reveal	.50	35	.85	64
SB-157	24 x 24 x 5/8	Trim	.50	35	.85	64
SB-197	24 x 48 x 5/8	Trim	.50	35	.85	64
Protectone® (For specific UL fire resistance time-rated assemblies)						
PSB-154	24 x 24 x 5/8	Reveal	.55	35	.85	64
PSB-157	24 x 24 x 5/8	Trim	.55	35	.85	64
PSB-197	24 x 48 x 5/8	Trim	.55	40	.85	64

ASTM E 1264 Classification: Type III, Form 2, Pattern C D


Edge Detail Options



BioShield™
BioShield treatment **included** for added mold and mildew resistance.

Popular Applications:

- Schools • Dorms • Day Cares • Education



PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 2
3. Pattern C D
4. Non-directional fissured and perforated wet-felted lay-in panels with impact resistant coating.
5. Size 5/8" thick x [24"x 24"] [24"x 48"]
6. Edge Detail [Trim] [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) [.50] [.55]
8. Ceiling Attenuation Class (CAC) [35] [40]
9. Light Reflectance Coefficient (LR) .85
Light Reflectance Designation LR-1
10. Color White
11. Flame Spread Classification Class A
12. Underwriters Laboratories Inc. Fire-Resistance Time-Rated Assembly* [D203] [D205] [G208] [G218] [G248] [G255] [L201] [P204] [P259] [P260] [P261] [P262] [P264]
13. Manufacturer, subject to compliance with requirements of this specification, BPB.
14. Product Name Celotex® Brand [School Board®] [Protectone® School Board®]

* Relevant to Protectone only. Refer to UL Fire Resistance Directory for specific design information.

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogden Dale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4785 Rev.D/5M/0705

