

Architectural Abstract

Stippled Unperforated WET-FELTED ACOUSTICAL CEILING PANELS

- Suitable where embossed pattern ceiling is desired.
- TMU and PTU with PlastiGard™ Option meet the USDA/FSIS guideline requirements for use in federally inspected food processing establishments.
- PlastiGard™ finish available for a scrubbable/washable surface.

See reverse side for additional product specifications.




Item Number	Nominal Size (Inches)	Edge Detail	UL Classified NRC	CAC	LR	Sq. Ft. Per Carton
Safetone® Class A						
TMU-157	24 x 24 x 5/8	Trim	-	35	.83	64
TMU-197*	24 x 48 x 5/8	Trim	-	35	.83	64
Protectone® (For specific UL fire resistance time-rated assemblies)						
PTU-157	24 x 24 x 5/8	Trim	-	40	.83	64
PTU-197*	24 x 48 x 5/8	Trim	-	40	.83	64

ASTM E 1264 Classification: Type III, Form 2, Pattern E
Type IX, Form 2, Pattern E (PlastiGard Finish)

*Specify "PG" after item number for PlastiGard option. Example: TMU-197-PG

Edge Detail



Trim Edge
(Square) 1/8" Grid



Popular Applications:

- Restaurants • Food Processing • Healthcare



PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type [III] [IX (PlastiGard)]
2. Form 2
3. Pattern E
4. Wet-felted unperforated stippled surface
5. Size 5/8" x [24"x 24"] [24"x 48"]
6. Edge Detail Trim
7. Noise Reduction Coefficient (NRC) N/A
8. Ceiling Attenuation Class (CAC) [35] [40]
9. Light Reflectance Coefficient (LR) .83
Light Reflectance Designation LR-1
10. Color White
11. Flame Spread Classification Class A
12. Underwriters Laboratories Inc. Fire-Resistance Time-Rated Assembly*
[D203] [D205] [G208] [G218] [G248] [G255] [L201] [P204] [P259] [P260] [P261] [P262]
[P264] [P266]
13. Manufacturer, subject to compliance with requirements of this specification, BPB
14. Product Name Celotex® Brand [Stippled Unperforated]
[Protectone® Stippled Unperforated]

* Relevant to Protectone only. Refer to UL Fire Resistance Directory for specific design information.

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogdendale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4743 Rev. F/10M/0505

