

Architectural Abstract

Symphony® *f* FIBERGLASS CEILINGS

- Reinforced mat-faced fiberglass panel.
- Exceptional durability/scrubbability.
- Luxurious, smooth-textured surface plus superior noise reduction to maximize interzone attenuation.
- Perfect for exceptional speech privacy and enhanced productivity in open plan environments.
- Outstanding acoustical and thermal value, high light reflectance and humidity resistance.
- Mix with Symphony® *g*, Symphony® *m* and TufCore™ (White Overtone® Finish) products to achieve "checkerboarding".*



Item Number	Nominal Size (Inches)	Edge Detail	R-value	NRC	AC	CAC†	LR	Sq. Ft. Per Carton
Safetone® Class A								
1322-OVT-1	24 x 24 x 3/4	Trim	3.4	.85	190	20	.89	64
1320-OVT-1	24 x 48 x 3/4	Trim	3.4	.85	190	20	.89	128
1347-OVT-1	20 x 60 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	100
1342-OVT-1	24 x 24 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	48
1340-OVT-1	24 x 48 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	96
1341-OVT-1	24 x 60 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	120
1346-OVT-1	24 x 96 x 1	Trim	4.3	.95	200	25	.89	192
1343-OVT-1	30 x 30 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	75
1349-OVT-1	30 x 60 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	150
1344-OVT-1	48 x 48 x 1	Trim, Reveal, Narrow Reveal	4.3	.95	200	25	.89	192
1345-OVT-1	48 x 60 x 1	Trim	4.3	.95	200	25	.89	240
1348-OVT-1	48 x 96 x 1	Trim	4.3	.95	200	25	.89	192
1367-OVT-1	20 x 60 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	67
1362-OVT-1	24 x 24 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	32
1360-OVT-1	24 x 48 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	64
1361-OVT-1	24 x 60 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	80
1366-OVT-1	24 x 96 x 1-1/2	Trim	6.5	1.00	210	25	.89	128
1363-OVT-1	30 x 30 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	50
1369-OVT-1	30 x 60 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	100
1364-OVT-1	48 x 48 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	128
1365-OVT-1	48 x 60 x 1-1/2	Trim	6.5	1.00	210	25	.89	160
1368-OVT-1	48 x 96 x 1-1/2	Trim	6.5	1.00	210	25	.89	128
1370-OVT-1	60 x 60 x 1-1/2	Trim, Reveal, Narrow Reveal	6.5	1.00	210	25	.89	200

ASTM E 1264 Classification: Type XII, Form 2, Pattern E
† With optional foil backing

Ordering Procedure: To order preferences for edge details and finishes, select the item number above, then add the appropriate Edge Detail Code below. For foil backing add F to code. Example:


Item Number	Edge Detail Code (Other than Trim)	Foil Backing
(See Chart)	B Reveal (15/16") F Narrow Reveal (9/16")	F (Leave blank for no foil backing)
Example: 1362-OVT-1	1362 B -OVT-1 1362 F -OVT-1	1362B-OVT-1 F 1362B-OVT-1

Finish




White Overtone®
OVT-1

Edge Detail Options



Trim Edge
(Square) 15/16" Grid

Reveal Edge
15/16" Grid



Narrow Reveal Edge
3/8" Grid



Popular Applications:

- Open Plan Areas • Offices • Restaurants
- Healthcare • Libraries • Galleries • Resorts



* **Checkerboarding:** Using similar aesthetic products in the same room, same offices, same building or same complex to achieve a consistent look while meeting various acoustical performance needs and budgets.

PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide acoustical ceiling material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

Size Options

24" x 24"

24" x 48"

24" x 60"

24" x 96"

48" x 48"

48" x 60"

48" x 96"

30" x 30"

20" x 60"

30" x 60"

60" x 60"

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XII
2. Form 2
3. Pattern E
4. Fine textured fiberglass lay-in panel with subtle Overtone® finish
5. Size [3/4"] [1"] [1-1/2"] thick x [24"x 24"] [24"x 48"] [24"x 60"] [24"x96"] [48"x48"] [48"x 60"] [48"x 96"] [30"x 30"] [20"x 60"] [30"x 60"] [60"x 60"]
6. Edge Detail [Trim(Square)] [Reveal] [Narrow Reveal]
7. Noise Reduction Coefficient (NRC) [.85] [.95] [1.00]
8. Articulation Class (AC) [190] [200] [210]
9. Ceiling Attenuation Class (CAC) with optional foil backing [20] [25]
10. Light Reflectance Coefficient (LR) .89
Light Reflectance Designation LR-1
11. Color: White
12. Flame Spread Classification Class A
13. Manufacturer, subject to compliance with requirements of this specification, BPB
14. Product Name Capaul® Brand Symphony® f

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogdendale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

®™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-3988 Rev. B/10M/0605

