

## Architectural Abstract

### Theatre Black

#### WET-FELTED ACOUSTICAL CEILING PANELS

- Specifically developed to meet acoustical & aesthetic requirements for theatre applications.
- Decorative while maintaining acoustical control.
- Rich black color creates a unique atmosphere from the typical white tile application.


See reverse side for additional product specifications.



| Item Number  | Nominal Size (Inches) | Edge Detail | UL Classified NRC | UL Classified CAC | LR | Sq. Ft. Per Carton |
|--|-----------------------|-------------|-------------------|-------------------|----|--------------------|
| <b>Safetone® Class A</b>   |                       |             |                   |                   |    |                    |
| NDP-157-Black  | 24 x 24 x 5/8         | Trim        | .55               | 33                | -  | 64                 |
| NDP-197-Black  | 24 x 48 x 5/8         | Trim        | .55               | 35                | -  | 64                 |
| <b>Protectone®</b> (For specific UL fire resistance time-rated assemblies) |                       |             |                   |                   |    |                    |
| PNP-157-Black  | 24 x 24 x 5/8         | Trim        | .55               | 35                | -  | 64                 |
| PNP-197-Black  | 24 x 48 x 5/8         | Trim        | .55               | 40                | -  | 64                 |

ASTM E 1264 Classification: Type III, Form 2, Pattern C

#### Edge Detail



**Trim Edge**  
(Square) 1<sup>5</sup>/<sub>16</sub>" Grid



#### BioShield™ Option

Mold and mildew guard available as an option.

#### Popular Applications:

- Theatres • School Auditoriums • Salons
- Galleries • Restaurants



# PRODUCT SPECIFICATION DETAILS

## ACOUSTICAL CEILING SYSTEMS

### 09500

## PART 2: PRODUCTS

### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

### 2.2 MATERIALS

Acoustical Ceiling Units:

1. Type III
2. Form 2
3. Pattern C
4. Non-directional perforated wet-felted lay-in panel, painted black.
5. Size 5/8" thick x [24"x 24"] [24"x 48"]
6. Edge Detail Trim
7. Noise Reduction Coefficient (NRC) .55
8. Ceiling Attenuation Class (CAC) [33] [35] [40]
9. Color Black
10. Flame Spread Classification Class A
11. Underwriters Laboratories Inc. Fire-Resistance Time-Rated Assembly\* [D203] [D205] [G208] [G218] [G248] [G255] [L201] [P204] [P259] [P260] [P261] [P262] [P264]
12. Manufacturer, subject to compliance with requirements of this specification, BPB
13. Product Name Celotex® Brand [Theatre Black] [Protectone® Theatre Black]

\*Relevant to Protectone Only. Refer to UL Fire Resistance Directory for specific design information.

Distributed by:

### USA

**BPB America Inc.**  
5301 West Cypress St., Suite 300  
Tampa, FL 33607  
Toll Free: +1-866-427-2872  
Fax: +1-800-829-1422  
E-mail: [crc@bpb-na.com](mailto:crc@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

### Canada

**BPB Canada Inc.**  
Architectural Products Sales Division  
6715 Ogden Dale Road SE  
Calgary, Alberta T2C 2A4  
Toll Free: +1-866-427-2872  
Fax: +1-800-829-1422  
E-mail: [crc@bpb-na.com](mailto:crc@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

### Outside North America

**BPB America Inc.**  
5301 West Cypress St., Suite 300  
Tampa, FL 33607  
Phone: +1-813-286-3900  
Fax: +1-813-286-3908  
E-mail: [international@bpb-na.com](mailto:international@bpb-na.com)  
Web: [www.bpb-na.com](http://www.bpb-na.com)

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4748 Rev.C/5M/0705

