

Architectural Abstract

TufCore 49™ GYPSUM CEILINGS


- Gypsum core with fiberglass mat.
- Acoustical performance and elegant appearance can now be balanced throughout the entire office space.
- Create a unified ceiling appearance by combining a high CAC gypsum core with premium finishes.
- Superior attenuation helps maintain speech privacy and improve workplace efficiency, while high light reflectance reduces eye fatigue.
- Great for "checkerboarding" with Tufcore™ and other Capaul® Brand products with like finishes.*



Item Number	Nominal Size (Inches)	Edge Detail	NRC	CAC	LR	Sq. Ft. Per Carton
White Nubby Fabric			Safetone® Class A			
1642-NBY-1	24 x 24 x 1/2	Trim	–	40	.85	32
1640-NBY-1	24 x 48 x 1/2	Trim	–	40	.85	32
White Elite Vinyl						
1642-ELT-1	24 x 24 x 1/2	Trim	–	40	.84	32
1640-ELT-1	24 x 48 x 1/2	Trim	–	40	.84	32

ASTM E 1264 Classification: Type XX, Pattern E (White Nubby)
Type XX, Pattern E I (White Nubby)

Edge Detail




Trim Edge
(Square) 15/16" Grid

Finishes



White Nubby
NBY-1



White Elite
ELT-1



Popular Applications:

- Open Plan Spaces with Adjacent Private Offices
- Conference Rooms • Production Areas



* **Checkerboarding:** Using similar aesthetic products in the same room, same offices, same building or same complex to achieve a consistent look while meeting various acoustical performance needs and budgets.

PRODUCT SPECIFICATION DETAILS

ACOUSTICAL CEILING SYSTEMS

09500

PART 2: PRODUCTS

2.1 GENERAL

Provide acoustical ceiling material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

1. Type XX
2. Form NA
3. Pattern [E] [E I]
4. Fine textured, fabric or perforated vinyl finish gypsum lay-in panel
5. Size 1/2" x [24"x 24"] [24"x 48"]
6. Edge Detail Trim (Square)
7. Noise Reduction Coefficient (NRC) NA
8. Articulation Class (AC) NA
9. Ceiling Attenuation Class (CAC) 40
10. Light Reflectance Coefficient (LR) [.84] [.85]
11. Color: White
12. Flame Spread Classification Class A
13. Manufacturer, subject to compliance with requirements of this specification, BPB
14. Product Name Capaul® Brand Tufcore 49™

Size Options

24"x 24"

24"x 48"

Distributed by:

USA

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Canada

BPB Canada Inc.
Architectural Products Sales Division
6715 Ogdendale Road SE
Calgary, Alberta T2C 2A4
Toll Free: +1-866-427-2872
Fax: +1-800-829-1422
E-mail: crc@bpb-na.com
Web: www.bpb-na.com

Outside North America

BPB America Inc.
5301 West Cypress St., Suite 300
Tampa, FL 33607
Phone: +1-813-286-3900
Fax: +1-813-286-3908
E-mail: international@bpb-na.com
Web: www.bpb-na.com

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

©2005 BPB America Inc. Printed in U.S.A. Form LCD-4012 Rev. B/10M/0605

