



- GENERAL NOTES-
1. CLOSER SIZE: 12 1/4 x 3 1/2 x 2 5/32 (2 3/8 WITH DROP PLATE).
 2. LOCATE CLOSER & TRACK FROM CL OF PIVOT OR SWING CLEAR HINGE PIN IF USED.
 3. REINFORCING PER ANSI/SDI-100 RECOMMENDED FOR HOLLOW METAL DOORS AND FRAMES.
 4. TAMPER RESISTANT TORX MACHINE SCREWS SUPPLIED BY LCN
 5. MAXIMUM BUTT SIZE 5" x 5".

AUXILIARY STOP RECOMMENDED

INCH	1/4	1/2	5/8	11/16	7/8	15/16	1 3/8	1 1/2
M.M.	6	13	16	17	22	24	35	38
INCH	2 1/8	2 5/32	2 5/16	2 3/8	2 1/2	2 3/4	3	3 7/16
M.M.	54	55	59	60	64	70	76	87
INCH	3 1/2	4	5	5 1/4	6	8 1/4	12 1/4	24 1/2
M.M.	89	102	127	133	152	210	311	622

No.	REVISION	BY	DATE
2	TEMPLATE UPDATE	JEJ	6/96

LCN®

APP BY JEJ 6/96
DO NOT SCALE

SECURITY CLOSER WITH TRACK (PUSH SIDE MOUNTED) ON DOOR OR DROP PLATE

4210 T